

Kerlite Plus - Oaks

General: Kerlite Plus Oaks recaptures the natural appeal & charm of wood, with all the benefits of technologically advanced and aesthetically innovative ceramics. Architects and Decorators can create whatever design proposals they desire from this unique material, and with a tough fibre glass backing, Kerlite Plus Oaks can be installed directly over existing flooring in wood, ceramic or any other compact type surface. These 4 new timber colours in the Kerlite family is the latest step forward in design technology.

Applications: Commercial & residential indoor floors, including boats, buildings, foyers, boutiques, galleries, living areas, kitchens and bathrooms, plus all wall applications, splashbacks, bench tops, lift cars and external walls (inclusive of wall cladding)



Origin:	Italy		
Colours:	Timber	(limewash)	
	Rain	(grey)	
	Land	(beech)	
	Fossil	(ebony)	
Sizes:	1000 x 1000 mm	1000 x 3000 mm	1500 x 200 mm 1000 x 142 mm
Thickness:	Kerlite Plus 3.5mm (K+) wall & floor		
Finishes:	Timber grain surface feel		
Type:	Full-bodied vitrified porcelain with rectified edges		
Appearance:	Natural wood grain with smooth surface feel		
Production:	Pure phosphate & clay with zirconium, Kerlite Plus fibre glass backed.		
Technical:	Water Absorption less than 0.01% Frost Resistant (No visible fault) & Scratch Resistant Stain Resistant (Class 5) & Graffiti Proof Surface Hardness – MOHS 7 (of 10) Grade (PEI) 5 – All Residential, All Commercial Fire Retardant – Kerlite Rating “Class 0”, Kerlite Plus “Class 1” Weight – 7.1 kg m ² + Flexible - radius curvature of 5 metres		
Slip Resistance:	R9 (DIN 51130) Australian Standard AS/NZS 4586-2004 - Average Pendulum Number achieved by Wet Test - 40 - Classification of Floor Surface in Wet Condition - X - Risk of Slipping when Floor Surface is Wet - Moderate		
Guarantee:	20 Years – for residential & commercial applications		